

ST 37 K DIN 10277 / 671

ROND

6	12	16	22	26	32	38	50	65	80	110	140	170	200
8	14	18	24	28	35	40	55	70	90	120	150	180	
10	15	20	25	30	36	45	60	75	100	130	160	190	

ST 37 K DIN 10277 / 174

PLAT

	2	3	4	5	6	8	10	12	15	20	25	30	40	50	60
15	10	8	10	10	10	12	15	20	25	30	35	50	60	80	
18	12	10	12	12	12	15	18	25	30	40	40	60	70	100	
20	15	12	15	15	15	18	20	30	35	50	50	70	80		
25	18	15	18	18	18	20	25	35	40	60	60	80	100		
30	20	18	20	20	20	25	30	40	45	70	70	100	120		
40	25	20	25	25	25	30	35	45	50	80	80	120	150		
	30	25	30	30	30	35	40	50	55	90	90	150	200		
	40	30	35	35	35	40	45	55	60	100	100	200	250		
	50	35	40	40	40	45	50	60	70	120	120	250	300		
		40	45	45	45	50	60	70	80	150	130	300	350		
		50	50	50	50	55	70	80	90	160	150	350	400		
		60	60	55	55	60	80	90	100	180	160	400	500		
		80	70	60	60	70	90	100	110	200	180	500			
			80	70	70	80	100	110	120	250	200				
			90	80	80	90	120	120	140	300	250				
			100	90	90	100	140	140	150	350	300				
			120	100	100	120	150	150	160	400	350				
			150	120	120	140	160	160	180	500	400				
				150	150	150	180	180	200		500				
					200	160	200	200	250						
						180	250	250	300						
						200	300	300	350						
						250	350	350	400						
						300	400	400	500						
						350		500							
						400									

ST 37 K DIN 10277 / 178

VIERKANT

8	12	15	18	22	30	40	55	65	80	100	120
10	14	16	20	25	35	50	60	70	90	110	150

Afwijkende afmetingen op korte termijn leverbaar, of zagen wij uit bovenstaande afmetingen.

Speciale profielen op aanvraag.

Blankstaal

Ongelegeerde blankstalen in koud getrokken **niet** gegloeide uitvoering. Staflengte: 3 - 3,2 mtr. resp. 5,5 - 6,5 mtr.