

1.2379 Vervolg

GESLEPEN STAFSTAAL DIN 59350 STANDAARD LENGTE 500 MM

	2,2	3,2	4,2	5,2	6,2	8,2	10,4	12,4	15,4	20,4	25,4	30,4	40,4	50,4
10,3	X	X	X	X	X	X								
15,3	X	X	X	X	X	X	X	X						
20,3	X	X	X	X	X	X	X	X	X					
25,3	X	X	X	X	X	X	X	X	X	X				
30,3	X	X	X	X	X	X	X	X	X	X	X			
40,3	X	X	X	X	X	X	X	X	X	X	X	X		
50,3	X	X	X	X	X	X	X	X	X	X	X	X	X	
60,3	X	X	X	X	X	X	X	X	X	X	X	X	X	X
80,3	X	X	X	X	X	X	X	X	X	X	X	X	X	X
100,3	X	X	X	X	X	X	X	X	X	X	X	X	X	X
125,3	X	X	X	X	X	X	X	X	X	X	X	X	X	X
150,3	X	X	X	X	X	X	X	X	X	X	X	X	X	X
200,3	X	X	X	X	X	X	X	X	X	X	X	X	X	X
250,3	X	X	X	X	X	X	X	X	X	X	X	X	X	X
300,3	X	X	X	X	X	X	X	X	X	X	X	X	X	X

Toleranties: dikte + 0,2 / - 0 mm, breedte + 0,2 / - 0 mm, lengte + 5 mm

VIERKANT 6,2 8,2 10,4 12,4 15,4 20,4 25,4 30,4 40,4 50,4

X	X	X	X	X	X	X	X	X	X	X
---	---	---	---	---	---	---	---	---	---	---

Tolerantie van de doorsnede: + 0,2 mm

GESLEPEN STAFSTAAL LENGTE 1030 MM

breedte / dikte	2,4	3,4	4,4	5,4	6,4	8,4	10,4	12,4	15,4	16,4	20,4	25,4	30,4	32,4	40,4	50,4	60,4	63,4	70,4	80,4	100,4	
10,4	X	X	X	X	X	X																
15,4	X	X	X	X	X	X	X	X														
20,4	X	X	X	X	X	X	X	X	X	X												
25,4	X	X	X	X	X	X	X	X	X	X	X											
30,4	X	X	X	X	X	X	X	X	X	X	X	X										
32,4	X	X	X	X	X	X	X	X	X	X	X	X	X									
40,4	X	X	X	X	X	X	X	X	X	X	X	X	X	X								
50,4	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X							
60,4	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X						
63,4	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X					
70,4	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X				
80,4	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X			
90,4	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X		
100,4	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	
125,4	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X
150,4	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X
160,4	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X
175,4	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X
200,4	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X
250,4	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X
300,4	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X
350,4										X	X	X	X	X	X	X	X	X				
400,4										X	X	X	X	X	X	X	X	X				

Toleranties: dikte + 0,25 / - 0 mm, breedte + 0,4 / - 0 mm, lengte + 10 mm

VIERKANT 6,4 8,4 10,4 12,4 15,4 16,4 20,4 25,4 30,4 32,4 40,4 50,4 60,4 63,4 70,4 80,4 100,4 120,4 150,4

X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X
---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---

Tolerantie van de doorsnede: + 0,25 mm

Prijslijst op aanvraag.

Afwijkende afmetingen/toleranties zijn op korte termijn leverbaar.